

PNEUMATIC CASTERS

- Wheel sizes from 8" to 12".
- Top plate and fork 1/4" cold forged steel.
- Double ball bearing swivel raceway, heat treated for long wear and added strength.
- Yoke with bright zinc plate.
- The pneumatic casters are designed for platform cart use, quiet moving and easy rolling.
- Load capacities from 220 lbs. to 440 lbs.



SCAFFOLD CASTERS

- Double ball bearing.
- Cast iron core/hard rubber wheel or PU wheel.
- Thread and swivel locking mechanism.



TRUCK CASTERS



SPRING -LOADED CASTERS

- Swivel bracket with thrust bearing and taper ball bearing in the swivel head.
- Bracket and spring hinged plate of very strong construction to reliably compensate.
- Tire made of solid rubber elastic, wheel center in strong steel welded construction vulcanized to wheel center, with precision ball bearing.
- Load capacities from 352 lbs. to 1980 lbs.



INSTITUTIONAL EQUIPMENT CASTERS

- Wheel sizes from 75mm to 200mm.
- Wheel type: PPU, PPR, Anti-static, Rubber, (plastic steel/steel frame with 25mm width), (steel with 28mm width).
- Mounting parts: plate, threaded stem, bolt hole or socket. Swivel, rigid or total lock.
- Housing made of pressed steel, bright zinc-plated, chrome-plated, black-coated or brass plated.



HEAVY DUTY CASTERS

- Wheel sizes from 4" to 10".
- Wheel type: mold on rubber wheel on cast iron center, mold on polyurethane on cast iron center or cast iron wheel.
- Wheel center in extra strong welded construction, four folded welded.
- Blue painted, grease fitting in yoke base.
- Carbon steel ball bearings.
- Recommended for maximum protection to load and floor.
- Wheel type: Rubber (NBR) Wheels, Nylon (MRC) Wheels, PU wheels.



LIGHT DUTY CASTERS

- Wheel sizes from 2" to 4".
 - Wheel type: hard/soft rubber, nylon, plastic or cast iron.
 - Mounting parts: plate or threaded stem.
 - Swivel, rigid or total lock
 - Yoke with bright zinc-plated
 - Shopping carts, portable storage racks, lighter general duty use.
 - Load capacities from 66 lbs. to 154 lbs.
-
- Wheel sizes from 2 1/2" to 5".
 - Wheel type: soft rubber, nylon, plastic or cast iron.
 - Mounting parts: friction ring stem.
 - Swivel, Rigid or Total lock.
 - Yoke with bright zinc-plated
 - Shopping carts, portable storage racks, lighter general duty use.
 - Load capacities from 60 lbs. to 132 lbs.



MEDIUM DUTY CASTERS

- Wheel sizes from 4" to 8".
- Double ball bearing raceway heat treated for long wear and added strength.
- Yoke with bright zinc-plated. Swivel, rigid or swivel with brake grease fitting in swivel raceway and wheel.
- 1/2" diameter axle bolt with lock nut.
- 3/4" roller bearings.
- Wheel type: Mold on rubber, mold on polyurethane, phenolic, v-groove, TPR, TPU, solid elastic rubber.



MEDIUM DUTY CASTERS - OPTIONS



Roller Bearing

Rubber wheel

PU wheel



Phenolic wheel PPR wheel



PPU wheel

PP wheel

Cast Iron wheel

Swivel 6X2 Yoke w/ 6x2 PU wheel



Specification:

- 6" in diameter
- 2" in width
- 2 seal ball bearing
- Bearing Bore 1/2"
- PU tread
- Polyolefin core
- Load Capacity: 500 lbs
- Swivel Yoke
- Plate thickness: 0.235"± or 3 GA±
- Top Plate Size: 4 X 4-1/2"
- Bolt Hole Pattern: 2-5/8"~3" X 3~3-5/8"

Usage: Furniture/utility cart.

Rigid 6X2 Yoke w/ 6x2 PU wheel



Specification:

- 6" in diameter
- 2" in width
- 2 seal ball bearing
- Bearing Bore 1/2"
- PU tread
- Polyolefin core
- Load Capacity: 500 lbs
- Rigid Yoke
- Plate thickness: 0.235" or 3 GA
- Top Plate Size: 4 X 4-1/2"
- Bolt Hole Pattern: 2-5/8"~3" X 3~3-5/8"

Usage: Furniture/utility cart.

Swivel Plate 8x2 Yoke w/ 8X2 PU wheel



Specification:

- 8" in diameter
- 2" in width
- 2 seal ball bearing
- Bearing Bore 1/2"
- PU tread
- Polyolefin core
- Load Capacity: 500 lbs
- Swivel Yoke
- Plate Thickness: .235"± or 3 GA±
- Top Plate Size: 4" x 4-1/2"
- Bolt Hole Pattern: 2-5/8"~3" x 3~3-5/8"

Usage: U-Boat, roller container, and transportation carts.

Rigid Plate 8x2 Yoke w/ 8X2 PU wheel



Specification:

- 8" in diameter
- 2" in width
- 2 seal ball bearing
- Bearing Bore 1/2"
- PU tread
- Polyolefin core
- Load Capacity: 500 lbs
- Rigid Yoke
- Plate Thickness: .235"± or 3 GA±
- Top Plate Size: 4" x 4-1/2"
- Bolt Hole Pattern: 2-5/8"~3" x 3~3-5/8"

Usage: U-Boat, roller container, and transportation carts.